


N-Channel MOSFET


Features

- $R_{DS(on)}$ (Max 0.26 Ω) @ $V_{GS} = 10V$
- Gate Charge (Typical 90nC)
- Improved dv/dt Capability, High Ruggedness
- 100% Avalanche Tested
- Maximum Junction Temperature Range (150°C)



General Description

This Power MOSFET is manufactured advanced planar stripe, DMOS technology. This latest technology has been especially designed to minimize on-state resistance, have a high rugged avalanche characteristics. These devices are well suited for high efficiency switch mode power supplies, active power factor correction, electronic lamp ballasts based on half bridge topology.



Absolute Maximum Ratings

Symbol	Parameter	Value	Units
V_{DSS}	Drain to Source Voltage	500	V
I_D	Continuous Drain Current(@ $T_C = 25^\circ C$)	20	A
	Continuous Drain Current(@ $T_C = 100^\circ C$)	13	A
I_{DM}	Drain Current Pulsed (Note 1)	80	A
V_{GS}	Gate to Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	1110	mJ
E_{AR}	Repetitive Avalanche Energy (Note 1)	25.0	mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)	4.5	V/ns
P_D	Total Power Dissipation(@ $T_C = 25^\circ C$)	250	W
	Derating Factor above 25 °C	2.00	W/°C
T_{STG}, T_J	Operating Junction Temperature & Storage Temperature	-55 ~ 150	°C
T_L	Maximum Lead Temperature for soldering purpose, 1/8 from Case for 5 seconds.	300	°C

Thermal Characteristics

Symbol	Parameter	Value			Units
		Min.	Typ.	Max.	
R_{0JC}	Thermal Resistance, Junction-to-Case	-	-	0.50	°C/W
R_{0CS}	Thermal Resistance, Case to Sink	-	0.24	-	°C/W
R_{0JA}	Thermal Resistance, Junction-to-Ambient	-	-	40	°C/W

Electrical Characteristics ($T_C = 25^\circ C$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	500	-	-	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature coefficient	$I_D = 250\mu A$, referenced to $25^\circ C$	-	0.6	-	$^\circ C$
I_{DSS}	Drain-Source Leakage Current	$V_{DS} = 500V, V_{GS} = 0V$	-	-	10	μA
		$V_{DS} = 400V, T_C = 125^\circ C$	-	-	100	μA
I_{GSS}	Gate-Source Leakage, Forward	$V_{GS} = 30V, V_{DS} = 0V$	-	-	100	nA
	Gate-source Leakage, Reverse	$V_{GS} = -30V, V_{DS} = 0V$	-	-	-100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	-	4.0	V
$R_{DS(ON)}$	Static Drain-Source On-state Resistance	$V_{GS} = 10V, I_D = 10A$	-	0.21	0.26	Ω
g_{fs}	Forward Transconductance	$V_{DS} = 50V, I_D = 10.0A$	-	15	-	S
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{GS} = 0V, V_{DS} = 25V, f = 1MHz$	-	3350	-	pF
C_{oss}	Output Capacitance		-	490	-	
C_{rss}	Reverse Transfer Capacitance		-	50	-	
Dynamic Characteristics						
$t_{d(on)}$	Turn-on Delay Time	$V_{DD} = 250V, I_D = 20.0A, R_G = 25\Omega$ (Note 4, 5)	-	60	-	ns
t_r	Rise Time		-	210	-	
$t_{d(off)}$	Turn-off Delay Time		-	170	-	
t_f	Fall Time		-	130	-	
Q_g	Total Gate Charge	$V_{DS} = 400V, V_{GS} = 10V, I_D = 20.0A$ (Note 4, 5)	-	90	-	nC
Q_{gs}	Gate-Source Charge		-	20	-	
Q_{gd}	Gate-Drain Charge(Miller Charge)		-	42	-	

Source-Drain Diode Ratings and Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit.
I_S	Continuous Source Current	Integral Reverse p-n Junction Diode in the MOSFET	-	-	20	A
I_{SM}	Pulsed Source Current		-	-	80	
V_{SD}	Diode Forward Voltage	$I_S = 20.0A, V_{GS} = 0V$	-	-	1.4	V
t_{rr}	Reverse Recovery Time	$I_S = 20.0A, V_{GS} = 0V, dI_F/dt = 100A/us$	-	370	-	ns
Q	Reverse Recovery Charge		-	380	-	

*** NOTES**

1. Repetitive rating : pulse width limited by junction temperature
2. L = 5.0mH, $I_{AS} = 20.0A$, $V_{DD} = 50V$, $R_G = 25\Omega$, Starting $T_J = 25^\circ C$
3. $I_{SD} \leq 20.0A$, $dI/dt \leq 200A/us$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ C$
4. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$
5. Essentially independent of operating temperature.