



**Advanced Power  
Electronics Corp.**


**AP9466GM**

**RoHS-compliant Product**

*N-CHANNEL ENHANCEMENT MODE*

*POWER MOSFET*

- ▼ Low On-resistance
- ▼ Simple Drive Requirement
- ▼ Fast Switching Characteristic




|              |                |
|--------------|----------------|
| $BV_{DSS}$   | 40V            |
| $R_{DS(ON)}$ | 13.5m $\Omega$ |
| $I_D$        | 10A            |

## Description

The Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The SO-8 package is universally preferred for all commercial-industrial surface mount applications and suited for low voltage applications such as DC/DC converters.



## Absolute Maximum Ratings

| Symbol                     | Parameter                             | Rating     | Units               |
|----------------------------|---------------------------------------|------------|---------------------|
| $V_{DS}$                   | Drain-Source Voltage                  | 40         | V                   |
| $V_{GS}$                   | Gate-Source Voltage                   | $\pm 20$   | V                   |
| $I_D@T_A=25^\circ\text{C}$ | Continuous Drain Current <sup>3</sup> | 10         | A                   |
| $I_D@T_A=70^\circ\text{C}$ | Continuous Drain Current <sup>3</sup> | 8.4        | A                   |
| $I_{DM}$                   | Pulsed Drain Current <sup>1</sup>     | 40         | A                   |
| $P_D@T_A=25^\circ\text{C}$ | Total Power Dissipation               | 2.5        | W                   |
|                            | Linear Derating Factor                | 0.02       | W/ $^\circ\text{C}$ |
| $T_{STG}$                  | Storage Temperature Range             | -55 to 150 | $^\circ\text{C}$    |
| $T_J$                      | Operating Junction Temperature Range  | -55 to 150 | $^\circ\text{C}$    |

## Thermal Data

| Symbol | Parameter   | Value | Unit                      |
|--------|---|-------|---------------------------|
| Rthj-a | Thermal Resistance Junction-ambient <sup>3</sup> Max. | 50    | $^\circ\text{C}/\text{W}$ |



## Electrical Characteristics @ $T_j=25^{\circ}\text{C}$ (unless otherwise specified)

| Symbol       | Parameter   | Test Conditions               | Min. | Typ. | Max.      | Units     |
|--------------|---|-------------------------------|------|------|-----------|-----------|
| $BV_{DSS}$   | Drain-Source Breakdown Voltage                            | $V_{GS}=0V, I_D=250\mu A$     | 40   | -    | -         | V         |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance <sup>2</sup>            | $V_{GS}=10V, I_D=10A$         | -    | -    | 13.5      | $m\Omega$ |
|              |   | $V_{GS}=4.5V, I_D=6A$         | -    | -    | 21        | $m\Omega$ |
| $V_{GS(th)}$ | Gate Threshold Voltage                                    | $V_{DS}=V_{GS}, I_D=250\mu A$ | 1    | -    | 3         | V         |
| $g_{fs}$     | Forward Transconductance                                  | $V_{DS}=10V, I_D=10A$         | -    | 9.9  | -         | S         |
| $I_{DSS}$    | Drain-Source Leakage Current ( $T_j=25^{\circ}\text{C}$ ) | $V_{DS}=40V, V_{GS}=0V$       | -    | -    | 1         | $\mu A$   |
|              | Drain-Source Leakage Current ( $T_j=70^{\circ}\text{C}$ ) | $V_{DS}=32V, V_{GS}=0V$       | -    | -    | 100       | $\mu A$   |
| $I_{GSS}$    | Gate-Source Leakage                                       | $V_{GS}=\pm 20V$              | -    | -    | $\pm 100$ | nA        |
| $Q_g$        | Total Gate Charge <sup>2</sup>                            | $I_D=10A$                     | -    | 14.4 | 23        | nC        |
| $Q_{gs}$     | Gate-Source Charge  | $V_{DS}=32V$                  | -    | 2.4  | -         | nC        |
| $Q_{gd}$     | Gate-Drain ("Miller") Charge                              | $V_{GS}=4.5V$                 | -    | 9.2  | -         | nC        |
| $t_{d(on)}$  | Turn-on Delay Time <sup>2</sup>                           | $V_{DS}=20V$                  | -    | 7.6  | -         | ns        |
| $t_r$        | Rise Time   | $I_D=1A$                      | -    | 6.4  | -         | ns        |
| $t_{d(off)}$ | Turn-off Delay Time                                       | $R_G=3.3\Omega, V_{GS}=10V$   | -    | 24   | -         | ns        |
| $t_f$        | Fall Time   | $R_D=20\Omega$                | -    | 9    | -         | ns        |
| $C_{iss}$    | Input Capacitance   | $V_{GS}=0V$                   | -    | 800  | 1280      | pF        |
| $C_{oss}$    | Output Capacitance  | $V_{DS}=25V$                  | -    | 170  | -         | pF        |
| $C_{rss}$    | Reverse Transfer Capacitance                              | $f=1.0\text{MHz}$             | -    | 140  | -         | pF        |
| $R_g$        | Gate Resistance   | $f=1.0\text{MHz}$             | -    | 1.3  | 2         | $\Omega$  |

## Source-Drain Diode

| Symbol   | Parameter                          | Test Conditions       | Min. | Typ. | Max. | Units |
|----------|------------------------------------|-----------------------|------|------|------|-------|
| $V_{SD}$ | Forward On Voltage <sup>2</sup>    | $I_S=2.1A, V_{GS}=0V$ | -    | -    | 1.2  | V     |
| $t_{rr}$ | Reverse Recovery Time <sup>2</sup> | $I_S=10A, V_{GS}=0V,$ | -    | 29   | -    | ns    |
| $Q_{rr}$ | Reverse Recovery Charge            | $dI/dt=100A/\mu s$    | -    | 25   | -    | nC    |

### Notes:

1. Pulse width limited by Max. junction temperature.
2. Pulse test
3. Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board,  $t \leq 10\text{sec}$ ;  $125^{\circ}\text{C/W}$  when mounted on Min. copper pad.

THIS PRODUCT IS AN ELECTROSTATIC SENSITIVE, PLEASE HANDLE WITH CAUTION.

THIS PRODUCT HAS BEEN QUALIFIED FOR CONSUMER MARKET. APPLICATIONS OR USES AS CRITERIAL COMPONENT IN LIFE SUPPORT DEVICE OR SYSTEM ARE NOT AUTHORIZED.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance  
v.s. Junction Temperature




Fig 5. Forward Characteristic of  
Reverse Diode




Fig 6. Gate Threshold Voltage v.s.  
Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform








Fig 12. Gate Charge Waveform



## Package Outline : SO-8



| SYMBOLS  | Millimeters |      |      |
|----------|-------------|------|------|
|          | MIN         | NOM  | MAX  |
| A        | 1.35        | 1.55 | 1.75 |
| A1       | 0.10        | 0.18 | 0.25 |
| B        | 0.33        | 0.41 | 0.51 |
| C        | 0.19        | 0.22 | 0.25 |
| D        | 4.80        | 4.90 | 5.00 |
| E1       | 3.80        | 3.90 | 4.00 |
| E        | 5.80        | 6.15 | 6.50 |
| L        | 0.38        | 0.71 | 1.27 |
| $\theta$ | 0           | 4.00 | 8.00 |
| e        | 1.27 TYP    |      |      |



- 1.All Dimension Are In Millimeters.
- 2.Dimension Does Not Include Mold Protrusions.

## Part Marking Information & Packing : SO-8

