




PJ
series

Low Impedance, For Switching Power Supplies



- Low impedance and high reliability withstanding 5000 hours load life at +105°C (3000 / 2000 hours for smaller case sizes as specified below).
- Capacitance ranges available based on the numerical values in E12 series under JIS.
- Ideally suited for use of switching power supplies.
- Compliant to the RoHS directive (2011/65/EU).




■ Specifications

Item	Performance Characteristics										
Category Temperature Range	-55 to +105°C (6.3 to 100V), -40 to +105°C (160 to 400V), -25 to +105°C (450V)										
Rated Voltage Range	6.3 to 450V										
Rated Capacitance Range	0.47 to 15000μF										
Capacitance Tolerance	±20% at 120Hz, 20°C										
Leakage Current	Rated Voltage (V)	6.3 to 100					160 to 450				
	Leakage current	After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4 (μA), whichever is greater.					CV ≤ 1000 : I = 0.1CV+40 (μA) max. (1 minute's) CV > 1000 : I = 0.04CV+100 (μA) max. (1 minute's)				
Tangent of loss angle (tan δ)	120Hz, 20°C										
	Rated Voltage (V)	6.3	10	16	25	35	50	63 to 100	160 to 350	400 · 450	
	tan δ (MAX.)	0.22	0.19	0.16	0.14	0.12	0.10	0.08	0.20	0.25	
For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.											
Stability at Low Temperature	Rated voltage (V)		6.3 · 10	16	25 · 35	50 to 100	160 · 200	250	315 · 350	400	450
	Impedance ratio (MAX.)	Z-25°C / Z+20°C	—	—	—	—	—	—	—	—	15
		Z-40°C / Z+20°C	—	—	—	—	4	6	8	10	—
		Z-55°C / Z+20°C	4	3	3	2	—	—	—	—	—
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 5000 hours (2000 hours for φD=5 and 6.3, 3000 hours for φD=8) at 105°C, the peak voltage shall not exceed the rated voltage.					Capacitance change	Within ±20% of the initial capacitance value				
						tan δ	200% or less than the initial specified value				
						Leakage current	Less than or equal to the initial specified value				
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.					Capacitance change	Within ±20% of the initial capacitance value				
						tan δ	150% or less than the initial specified value				
						Leakage current	Less than or equal to the initial specified value				
Marking	Printed with white color letter on dark brown sleeve.										

■ Radial Lead Type

Type numbering system (Example : 25V 470µF)



Type	Code
Small Dia	—
Low Profile	6
Size code	
Configuration ※	
Capacitance tolerance (±20%)	Configuration
Rated capacitance (470µF)	φ D Pb-free leadwire Pb-free PET sleeve
Rated voltage (25V)	5 DD
Series name	6.3 ED
Type	8 · 10 PD
	12.5 to 18 HD

α	(φD < 10) 1.0
	(φD ≥ 10) 1.5

	5	6.3	8	10	12.5	16	18
φD	5	6.3	8	10	12.5	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
φd	0.5	0.5	0.6	0.6	0.6 ⁹⁾	0.8	0.8


※ In case L > 25 for the φ12.5 dia. unit, lead dia. φd = 0.8mm.

- Frequency coefficient of rated ripple current

• Please refer to page 20 about the end seal configuration.

Please refer to page 20, 21, 22 about the formed or taped product spec.
Please refer to page 4 for the minimum order quantity.

- Dimension table in next pages.



■Dimensions

Cap. (μF)	V (Code) Size code Code	6.3 (0J)		10 (1A)		16 (1C)		25 (1E)		35 (1V)	
		—	6	—	6	—	6	—	6	—	6
22	220									5 × 11	
27	270									5 × 11	
33	330							5 × 11		6.3 × 11	
39	390							5 × 11		6.3 × 11	
47	470					5 × 11		6.3 × 11		6.3 × 11	
56	560					5 × 11		6.3 × 11		6.3 × 11	
68	680			5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
82	820			5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
100	101	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5	
120	121	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5
150	151	6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5
180	181	6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 15
220	221	6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 15
270	271	6.3 × 15		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15
330	331	6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15
390	391	8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 25	12.5 × 15
470	471	8 × 15	10 × 12.5	8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15
560	561	8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15
680	681	8 × 20	10 × 15	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15
820	821	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 25	18 × 15
1000	102	10 × 20	12.5 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20
1200	122	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25
1500	152	10 × 25	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20
1800	182	10 × 31.5	16 × 15	12.5 × 20	16 × 15	12.5 × 31.5	16 × 20	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25
2200	222	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5
2700	272	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25	16 × 40	18 × 35.5
3300	332	12.5 × 25	18 × 15	12.5 × 35.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 40	
3900	392	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 31.5	18 × 25	16 × 40	18 × 35.5		
4700	472	12.5 × 35.5	18 × 20	16 × 31.5	18 × 25	16 × 35.5	18 × 31.5	18 × 40			
5600	562	12.5 × 40	18 × 20	16 × 35.5	18 × 25	16 × 40	18 × 35.5				
6800	682	16 × 31.5	18 × 25	16 × 35.5	18 × 31.5	18 × 35.5					
8200	822	16 × 35.5	18 × 31.5	16 × 40	18 × 35.5	18 × 40					
10000	103	16 × 40	18 × 31.5	18 × 40							
12000	123	18 × 35.5									
15000	153	18 × 40									φ D × L (mm)

Cap. (μF)	V (Code) Size code Code	50 (1H)		63 (1J)		80 (1K)		100 (2A)	
		—	6	—	6	—	6	—	6
0.47	R47	5 × 11						5 × 11	
0.68	R68	5 × 11						5 × 11	
1	010	5 × 11						5 × 11	
1.5	1R5	5 × 11						5 × 11	
2.2	2R2	5 × 11						5 × 11	
3.3	3R3	5 × 11						5 × 11	
4.7	4R7	5 × 11				5 × 11		6.3 × 11	
6.8	6R8	5 × 11				5 × 11		6.3 × 11	
10	100	5 × 11		5 × 11		6.3 × 11		6.3 × 11	
12	120	5 × 11		5 × 11		6.3 × 11		6.3 × 11	
15	150	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
18	180	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
22	220	6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5	
27	270	6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5
33	330	6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5
39	390	6.3 × 11		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 15
47	470	6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	10 × 20	12.5 × 15
56	560	6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15
68	680	8 × 11.5		8 × 15	10 × 12.5	10 × 20	12.5 × 15	10 × 25	12.5 × 15
82	820	8 × 15	10 × 12.5	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15
100	101	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 25	12.5 × 15	10 × 31.5	16 × 15
120	121	8 × 20	10 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	16 × 15
150	151	10 × 20	12.5 × 15	10 × 25	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15
180	181	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	16 × 15	12.5 × 31.5	16 × 20
220	221	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 31.5	18 × 15	12.5 × 35.5	16 × 25
270	271	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20
330	331	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25
390	391	12.5 × 25	16 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5
470	471	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25	16 × 40	18 × 35.5
560	561	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 35.5	
680	681	12.5 × 35.5	16 × 20	16 × 31.5	18 × 25	16 × 40	18 × 31.5	18 × 40	
820	821	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 35.5			
1000	102	16 × 31.5	18 × 25	16 × 40	18 × 35.5	18 × 40			
1200	122	16 × 35.5	18 × 31.5	18 × 40					
1500	152	16 × 40	18 × 31.5						
1800	182	18 × 35.5							
2200	222	18 × 40							φ D × L (mm)

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

Dimension table for 160 to 450V products are shown in 237 page.

CAT.8100C

■ Standard Ratings

Cap. (μF)	Code	Item	6.3 (0J)									
			—				6					
			Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms)	
				20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
100	101	5 × 11	5 × 11	1.40	3.50	150	99					
120	121	5 × 11	5 × 11	1.10	2.80	175	115					
150	151	6.3 × 11	6.3 × 11	0.78	2.10	225	155					
180	181	6.3 × 11	6.3 × 11	0.60	1.50	250	175					
220	221	6.3 × 11	6.3 × 11	0.48	1.20	285	205					
270	271	6.3 × 15	6.3 × 15	0.39	1.00	370	275					
330	331	6.3 × 15	6.3 × 15	0.32	0.80	405	310					
390	391	8 × 11.5	8 × 11.5	0.27	0.68	445	345					
470	471	8 × 15	8 × 15	0.22	0.55	550	435	10 × 12.5	0.23	0.58	575	455
560	561	8 × 15	8 × 15	0.19	0.48	595	480	10 × 12.5	0.21	0.53	600	485
680	681	8 × 20	8 × 20	0.16	0.40	730	605	10 × 15	0.18	0.45	700	580
820	821	8 × 20	8 × 20	0.13	0.33	795	670	10 × 15	0.15	0.38	750	635
1000	102	10 × 20	10 × 20	0.12	0.30	950	820	12.5 × 15	0.13	0.33	890	765
1200	122	10 × 20	10 × 20	0.10	0.25	1020	895	12.5 × 15	0.12	0.30	950	835
1500	152	10 × 25	10 × 25	0.084	0.21	1220	1090	12.5 × 15	0.10	0.25	1020	915
1800	182	10 × 31.5	10 × 31.5	0.078	0.20	1370	1230	16 × 15	0.084	0.21	1270	1140
2200	222	10 × 31.5	10 × 31.5	0.066	0.17	1470	1320	16 × 15	0.078	0.20	1340	1200
2700	272	12.5 × 25	12.5 × 25	0.051	0.14	1590	1430	18 × 15	0.072	0.18	1500	1350
3300	332	12.5 × 25	12.5 × 25	0.045	0.11	1710	1530	18 × 15	0.065	0.16	1600	1440
3900	392	12.5 × 31.5	12.5 × 31.5	0.037	0.093	1910	1710	16 × 20	0.056	0.14	1720	1540
4700	472	12.5 × 35.5	12.5 × 35.5	0.034	0.085	2100	1890	18 × 20	0.050	0.13	1920	1720
5600	562	12.5 × 40	12.5 × 40	0.031	0.078	2270	2040	18 × 20	0.047	0.12	1980	1780
6800	682	16 × 31.5	16 × 31.5	0.029	0.073	2370	2130	18 × 25	0.039	0.098	2210	1980
8200	822	16 × 35.5	16 × 35.5	0.027	0.068	2550	2290	18 × 31.5	0.031	0.078	2390	2150
10000	103	16 × 40	16 × 40	0.025	0.063	2750	2470	18 × 31.5	0.028	0.070	2490	2240
12000	123	18 × 35.5	18 × 35.5	0.023	0.058	2820	2530					
15000	153	18 × 40	18 × 40	0.022	0.055	2960	2660					

Cap. (μF)	Code	Item	10 (1A)									
			—				6					
			Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA rms)	
				20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
68	680	5 × 11	5 × 11	1.30	3.30	155	97					
82	820	5 × 11	5 × 11	1.10	2.80	175	110					
100	101	6.3 × 11	6.3 × 11	0.84	2.10	210	135					
120	121	6.3 × 11	6.3 × 11	0.72	1.80	235	160					
150	151	6.3 × 11	6.3 × 11	0.55	1.40	265	185					
180	181	6.3 × 11	6.3 × 11	0.46	1.20	290	205					
220	221	6.3 × 15	6.3 × 15	0.38	0.95	370	270					
270	271	6.3 × 15	6.3 × 15	0.31	0.78	405	300					
330	331	8 × 11.5	8 × 11.5	0.26	0.65	460	350					
390	391	8 × 15	8 × 15	0.22	0.55	550	430	10 × 12.5	0.24	0.60	555	430
470	471	8 × 15	8 × 15	0.19	0.48	595	475	10 × 12.5	0.21	0.53	600	475
560	561	8 × 20	8 × 20	0.16	0.40	730	590	10 × 15	0.18	0.45	700	565
680	681	8 × 20	8 × 20	0.13	0.33	795	660	10 × 15	0.14	0.35	770	635
820	821	10 × 20	10 × 20	0.11	0.28	985	835	12.5 × 15	0.13	0.33	920	780
1000	102	10 × 20	10 × 20	0.096	0.24	1060	915	12.5 × 15	0.10	0.25	1040	895
1200	122	10 × 25	10 × 25	0.078	0.20	1280	1120	12.5 × 15	0.096	0.24	1060	930
1500	152	10 × 31.5	10 × 31.5	0.072	0.18	1440	1290	16 × 15	0.078	0.20	1330	1190
1800	182	12.5 × 20	12.5 × 20	0.057	0.14	1470	1320	16 × 15	0.072	0.18	1420	1270
2200	222	12.5 × 25	12.5 × 25	0.045	0.11	1710	1530	18 × 15	0.060	0.15	1600	1440
2700	272	12.5 × 31.5	12.5 × 31.5	0.036	0.090	1940	1740	16 × 20	0.051	0.13	1740	1560
3300	332	12.5 × 35.5	12.5 × 35.5	0.032	0.080	2180	1960	16 × 20	0.045	0.11	1850	1660
3900	392	12.5 × 40	12.5 × 40	0.030	0.075	2360	2120	18 × 20	0.041	0.10	2050	1840
4700	472	16 × 31.5	16 × 31.5	0.028	0.070	2420	2170	18 × 25	0.035	0.088	2250	2020
5600	562	16 × 35.5	16 × 35.5	0.026	0.065	2610	2340	18 × 25	0.033	0.083	2340	2100
6800	682	16 × 35.5	16 × 35.5	0.024	0.060	2680	2410	18 × 31.5	0.027	0.068	2540	2280
8200	822	16 × 40	16 × 40	0.023	0.058	2820	2530	18 × 35.5	0.025	0.063	2690	2420
10000	103	18 × 40	18 × 40	0.021	0.053	3040	2730					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap. (μF)		V (Code)		16 (1C)											
		Size code		—						6					
				Item		Case size φD × L (mm)		Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)		Impedance (Ω) MAX.	
		Code													
						20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz			20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
47	470	5 × 11		1.30	3.30	155	92								
56	560	5 × 11		1.10	2.80	175	105								
68	680	6.3 × 11		0.78	2.00	220	135								
82	820	6.3 × 11		0.66	1.70	240	155								
100	101	6.3 × 11		0.55	1.40	265	175								
120	121	6.3 × 11		0.45	1.10	290	195								
150	151	6.3 × 15		0.37	0.93	375	260								
180	181	6.3 × 15		0.31	0.78	405	285								
220	221	8 × 11.5		0.26	0.65	460	335								
270	271	8 × 15		0.22	0.55	550	410	10 × 12.5	0.22	0.55		575	430		
330	331	8 × 15		0.18	0.45	595	455	10 × 12.5	0.18	0.45		625	480		
390	391	8 × 20		0.16	0.40	730	570	10 × 15	0.16	0.40		730	570		
470	471	8 × 20		0.14	0.35	770	615	10 × 15	0.14	0.35		770	615		
560	561	10 × 20		0.12	0.30	950	770	12.5 × 15	0.13	0.33		920	745		
680	681	10 × 20		0.10	0.25	1020	845	12.5 × 15	0.11	0.28		985	815		
820	821	10 × 25		0.084	0.21	1220	1030	12.5 × 15	0.096	0.24		1060	895		
1000	102	10 × 31.5		0.072	0.18	1410	1210	16 × 15	0.084	0.21		1270	1090		
1200	122	12.5 × 20		0.060	0.15	1430	1250	16 × 15	0.072	0.18		1390	1220		
1500	152	12.5 × 25		0.048	0.12	1660	1490	18 × 15	0.066	0.17		1560	1400		
1800	182	12.5 × 31.5		0.039	0.10	1880	1690	16 × 20	0.054	0.14		1700	1530		
2200	222	12.5 × 31.5		0.034	0.085	2010	1800	16 × 20	0.048	0.12		1800	1620		
2700	272	12.5 × 35.5		0.031	0.078	2220	1990	16 × 25	0.040	0.10		2010	1800		
3300	332	12.5 × 40		0.028	0.070	2410	2160	18 × 20	0.039	0.10		2090	1880		
3900	392	16 × 31.5		0.027	0.068	2470	2220	18 × 25	0.034	0.085		2290	2060		
4700	472	16 × 35.5		0.025	0.063	2680	2410	18 × 31.5	0.028	0.070		2490	2240		
5600	562	16 × 40		0.024	0.060	2820	2530	18 × 35.5	0.027	0.068		2620	2350		
6800	682	18 × 35.5		0.022	0.055	2900	2610								
8200	822	18 × 40		0.021	0.053	3040	2730								

Cap. (μF)		V (Code)		25 (1E)											
		Size code		—						6					
				Item		Case size φD × L (mm)		Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)		Impedance (Ω) MAX.	
		Code													
						20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz			20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
33	330	5 × 11		1.30	3.30	155	88								
39	390	5 × 11		1.10	2.80	175	100								
47	470	6.3 × 11		0.84	2.10	210	125								
56	560	6.3 × 11		0.72	1.80	235	140								
68	680	6.3 × 11		0.57	1.40	260	160								
82	820	6.3 × 11		0.47	1.20	285	180								
100	101	6.3 × 15		0.39	0.98	370	245								
120	121	6.3 × 15		0.32	0.80	405	275								
150	151	8 × 11.5		0.26	0.65	460	320								
180	181	8 × 15		0.22	0.55	550	390	10 × 12.5	0.24	0.60		555	395		
220	221	8 × 15		0.18	0.45	625	455	10 × 12.5	0.21	0.53		600	435		
270	271	8 × 20		0.15	0.38	750	560	10 × 15	0.18	0.45		700	525		
330	331	8 × 20		0.13	0.33	795	610	10 × 15	0.15	0.38		750	575		
390	391	10 × 20		0.11	0.28	985	770	12.5 × 15	0.13	0.33		920	720		
470	471	10 × 20		0.10	0.25	1020	810	12.5 × 15	0.11	0.28		985	785		
560	561	10 × 25		0.084	0.21	1220	990	12.5 × 15	0.10	0.25		1060	860		
680	681	10 × 31.5		0.072	0.18	1420	1180	16 × 15	0.084	0.21		1270	1050		
820	821	12.5 × 20		0.059	0.15	1430	1210	16 × 15	0.079	0.20		1340	1130		
1000	102	12.5 × 25		0.048	0.12	1660	1430	18 × 15	0.066	0.17		1520	1310		
1200	122	12.5 × 25		0.043	0.11	1760	1550	18 × 15	0.061	0.15		1600	1400		
1500	152	12.5 × 31.5		0.035	0.088	1980	1780	16 × 20	0.050	0.13		1770	1590		
1800	182	12.5 × 35.5		0.032	0.080	2180	1960	16 × 25	0.041	0.10		1980	1780		
2200	222	12.5 × 40		0.029	0.073	2360	2120	18 × 20	0.040	0.10		2050	1840		
2700	272	16 × 31.5		0.027	0.068	2470	2220	18 × 25	0.034	0.085		2290	2060		
3300	332	16 × 35.5		0.025	0.063	2680	2410	18 × 31.5	0.029	0.073		2490	2240		
3900	392	16 × 40		0.023	0.058	2820	2530	18 × 35.5	0.026	0.065		2690	2420		
4700	472	18 × 40		0.022	0.055	2960	2660								

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap. (μF)	V (Code)	Size code	Item	35 (1V)									
				—				6					
				Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
					20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
22	220		5 × 11		1.30	3.30	160	85					
27	270		5 × 11		1.00	2.50	180	99					
33	330		6.3 × 11		0.78	2.00	225	125					
39	390		6.3 × 11		0.66	1.70	245	140					
47	470		6.3 × 11		0.54	1.40	270	160					
56	560		6.3 × 11		0.45	1.10	295	180					
68	680		6.3 × 15		0.37	0.93	370	230					
82	820		6.3 × 15		0.31	0.78	415	265					
100	101		8 × 11.5		0.26	0.65	460	305					
120	121		8 × 15		0.22	0.55	550	370	10 × 12.5	0.24	0.60	555	375
150	151		8 × 15		0.18	0.45	595	415	10 × 12.5	0.20	0.50	625	435
180	181		8 × 20		0.16	0.40	730	520	10 × 15	0.18	0.45	700	500
220	221		8 × 20		0.13	0.33	795	580	10 × 15	0.14	0.35	770	560
270	271		10 × 20		0.11	0.28	985	735	12.5 × 15	0.13	0.33	920	690
330	331		10 × 20		0.096	0.24	1060	810	12.5 × 15	0.10	0.25	1020	780
390	391		10 × 25		0.084	0.21	1220	955	12.5 × 15	0.096	0.24	1060	825
470	471		10 × 31.5		0.072	0.18	1420	1130	16 × 15	0.084	0.21	1270	1010
560	561		12.5 × 20		0.059	0.15	1430	1160	16 × 15	0.075	0.19	1360	1100
680	681		12.5 × 25		0.048	0.12	1660	1370	18 × 15	0.066	0.17	1540	1270
820	821		12.5 × 25		0.042	0.11	1760	1490	18 × 15	0.060	0.15	1620	1370
1000	102		12.5 × 31.5		0.035	0.088	1980	1710	16 × 20	0.050	0.13	1770	1530
1200	122		12.5 × 35.5		0.031	0.078	2180	1920	16 × 25	0.041	0.10	1980	1740
1500	152		12.5 × 40		0.029	0.073	2360	2120	18 × 20	0.040	0.10	2050	1840
1800	182		16 × 31.5		0.027	0.068	2470	2220	18 × 25	0.034	0.085	2290	2060
2200	222		16 × 35.5		0.024	0.060	2680	2410	18 × 31.5	0.028	0.070	2490	2240
2700	272		16 × 40		0.022	0.055	2900	2610	18 × 35.5	0.026	0.065	2690	2420
3300	332		18 × 40		0.021	0.053	3040	2730					

Cap. (μF)	V (Code)	Size code	Item	50 (1H)									
				—				6					
				Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
					20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
0.47	R47		5 × 11		31.0	80.0	22	11					
0.68	R68		5 × 11		21.0	55.0	28	14					
1	010		5 × 11		14.0	38.0	36	18					
1.5	1R5		5 × 11		9.80	28.0	45	22					
2.2	2R2		5 × 11		6.50	18.0	54	27					
3.3	3R3		5 × 11		4.60	12.0	66	33					
4.7	4R7		5 × 11		3.10	7.80	81	40					
6.8	6R8		5 × 11		2.50	6.30	91	45					
10	100		5 × 11		2.00	5.00	115	57					
12	120		5 × 11		1.70	4.30	125	62					
15	150		5 × 11		1.30	3.30	145	72					
18	180		5 × 11		1.10	2.80	155	79					
22	220		6.3 × 11		0.91	2.30	195	100					
27	270		6.3 × 11		0.74	1.90	215	115					
33	330		6.3 × 11		0.60	1.50	240	135					
39	390		6.3 × 11		0.50	1.30	260	150					
47	470		6.3 × 15		0.42	1.10	330	195					
56	560		6.3 × 15		0.35	0.88	360	220					
68	680		8 × 11.5		0.28	0.70	410	255					
82	820		8 × 15		0.22	0.55	500	320	10 × 12.5	0.23	0.58	510	330
100	101		8 × 20		0.18	0.45	620	410	10 × 15	0.21	0.53	580	385
120	121		8 × 20		0.16	0.40	670	455	10 × 15	0.17	0.43	640	435
150	151		10 × 20		0.13	0.33	820	570	12.5 × 15	0.14	0.35	785	545
180	181		10 × 20		0.11	0.28	890	635	12.5 × 15	0.12	0.31	845	605
220	221		10 × 25		0.098	0.25	1040	760	12.5 × 15	0.10	0.25	920	670
270	271		10 × 31.5		0.085	0.21	1200	900	16 × 15	0.091	0.23	1120	840
330	331		10 × 31.5		0.072	0.18	1300	995	16 × 15	0.078	0.20	1210	925
390	391		12.5 × 25		0.053	0.13	1440	1120	16 × 15	0.072	0.18	1270	990
470	471		12.5 × 25		0.048	0.12	1500	1190	18 × 15	0.060	0.15	1470	1170
560	561		12.5 × 31.5		0.040	0.10	1680	1360	16 × 20	0.053	0.13	1550	1260
680	681		12.5 × 35.5		0.036	0.090	1850	1530	16 × 20	0.048	0.12	1630	1350
820	821		12.5 × 40		0.033	0.083	2010	1700	18 × 20	0.043	0.11	1810	1530
1000	102		16 × 31.5		0.030	0.075	2120	1830	18 × 25	0.036	0.090	2000	1730
1200	122		16 × 35.5		0.028	0.070	2260	1990	18 × 31.5	0.031	0.078	2140	1880
1500	152		16 × 40		0.026	0.065	2410	2170	18 × 31.5	0.029	0.073	2220	1990
1800	182		18 × 35.5		0.025	0.063	2460	2210					
2200	222		18 × 40		0.024	0.060	2560	2300					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap. (μF)	V (Code)	Size code	Item	63 (1J)									
				—				6					
				Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
					20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
10	100		5 × 11	1.60	4.00		135	67					
12	120		5 × 11	1.40	3.50		145	72					
15	150		6.3 × 11	1.10	2.80		185	92					
18	180		6.3 × 11	0.95	2.40		195	100					
22	220		6.3 × 11	0.78	2.00		215	110					
27	270		6.3 × 11	0.64	1.60		240	130					
33	330		6.3 × 15	0.52	1.30		305	170					
39	390		6.3 × 15	0.45	1.10		330	190					
47	470		8 × 11.5	0.37	0.93		365	215					
56	560		8 × 15	0.31	0.78		450	275	10 × 12.5	0.34	0.85	450	275
68	680		8 × 15	0.26	0.65		500	315	10 × 12.5	0.28	0.70	495	310
82	820		8 × 20	0.22	0.55		600	385	10 × 15	0.24	0.60	580	375
100	101		10 × 20	0.18	0.45		750	495	12.5 × 15	0.20	0.50	695	460
120	121		10 × 20	0.15	0.38		820	555	12.5 × 15	0.18	0.45	750	510
150	151		10 × 25	0.13	0.33		950	665	12.5 × 15	0.14	0.35	845	590
180	181		10 × 31.5	0.11	0.28		1110	790	16 × 15	0.12	0.30	1050	750
220	221		12.5 × 20	0.094	0.24		1140	835	16 × 15	0.10	0.25	1120	820
270	271		12.5 × 25	0.081	0.20		1340	1000	18 × 15	0.088	0.22	1290	965
330	331		12.5 × 25	0.072	0.18		1420	1090	18 × 15	0.078	0.20	1410	1080
390	391		12.5 × 31.5	0.059	0.15		1620	1260	16 × 20	0.070	0.18	1500	1170
470	471		12.5 × 35.5	0.052	0.13		1780	1420	16 × 25	0.063	0.16	1700	1350
560	561		12.5 × 40	0.047	0.12		1950	1580	18 × 20	0.058	0.15	1730	1400
680	681		16 × 31.5	0.043	0.11		2050	1700	18 × 25	0.051	0.13	1940	1610
820	821		16 × 35.5	0.040	0.10		2220	1880	18 × 31.5	0.043	0.12	2110	1780
1000	102		16 × 40	0.037	0.093		2370	2050	18 × 35.5	0.040	0.10	2280	1970
1200	122		18 × 40	0.034	0.085		2510	2210					

Cap. (μF)	V (Code)	Size code	Item	80 (1K)									
				—				6					
				Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)	
					20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
4.7	4R7		5 × 11	4.20	11.00		53	26					
6.8	6R8		5 × 11	2.60	7.00		68	34					
10	100		6.3 × 11	1.70	4.60		87	43					
12	120		6.3 × 11	1.40	3.80		96	48					
15	150		6.3 × 11	1.20	3.20		104	52					
18	180		6.3 × 11	1.00	2.70		114	58					
22	220		6.3 × 15	0.77	2.10		135	71					
27	270		6.3 × 15	0.63	1.70		149	80					
33	330		8 × 11.5	0.53	1.40		234	132					
39	390		8 × 15	0.46	1.20		272	156	10 × 12.5	0.49	1.30	271	155
47	470		8 × 15	0.39	1.10		295	175	10 × 12.5	0.42	1.10	293	174
56	560		8 × 20	0.34	0.92		347	208	10 × 15	0.36	0.97	337	202
68	680		10 × 20	0.28	0.76		426	264	12.5 × 15	0.31	0.84	402	249
82	820		10 × 20	0.25	0.68		447	284	12.5 × 15	0.27	0.73	430	273
100	101		10 × 25	0.21	0.57		526	347	12.5 × 15	0.23	0.62	466	308
120	121		10 × 31.5	0.18	0.49		606	406	16 × 15	0.20	0.54	663	444
150	151		10 × 31.5	0.15	0.41		663	459	16 × 15	0.18	0.47	699	484
180	181		12.5 × 25	0.13	0.35		734	520	16 × 15	0.15	0.41	766	543
220	221		12.5 × 31.5	0.12	0.32		816	595	18 × 15	0.13	0.35	881	643
270	271		12.5 × 31.5	0.10	0.27		894	667	16 × 20	0.11	0.30	995	742
330	331		12.5 × 35.5	0.088	0.24		1000	767	16 × 25	0.099	0.27	1140	874
390	391		12.5 × 40	0.078	0.21		1060	822	18 × 20	0.089	0.24	1170	908
470	471		16 × 31.5	0.069	0.19		1450	1150	18 × 25	0.080	0.22	1330	1060
560	561		16 × 35.5	0.062	0.17		1600	1300	18 × 31.5	0.072	0.19	1490	1210
680	681		16 × 40	0.055	0.15		1770	1470	18 × 31.5	0.065	0.18	1560	1300
820	821		18 × 35.5	0.049	0.13		1890	1590					
1000	102		18 × 40	0.044	0.12		2080	1790					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

■ Standard Ratings

Cap. (μF)	Code	Item	100 (2A)									
			—					6				
			Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA _{rms})		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mA _{rms})	
				20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	−10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
0.47	R47	5 × 11	43.0		116.0	17	8					
0.68	R68	5 × 11	23.0		62.0	23	11					
1	010	5 × 11	17.0		46.0	27	13					
1.5	1R5	5 × 11	10.0		27.0	35	17					
2.2	2R2	5 × 11	6.60		18.0	43	21					
3.3	3R3	5 × 11	4.10		11.0	54	27					
4.7	4R7	6.3 × 11	2.80		7.60	68	34					
6.8	6R8	6.3 × 11	1.90		5.10	83	41					
10	100	6.3 × 11	1.20		3.20	104	52					
12	120	6.3 × 11	1.00		2.70	114	57					
15	150	6.3 × 15	0.81		2.20	131	65					
18	180	6.3 × 15	0.67		1.80	155	80					
22	220	8 × 11.5	0.55		1.50	230	122					
27	270	8 × 15	0.47		1.30	269	146	10 × 12.5	0.50	1.40	268	145
33	330	8 × 15	0.38		1.00	299	169	10 × 12.5	0.42	1.10	293	166
39	390	8 × 20	0.33		0.89	352	202	10 × 15	0.36	0.97	337	193
47	470	10 × 20	0.28		0.76	423	252	12.5 × 15	0.31	0.84	402	239
56	560	10 × 20	0.24		0.65	456	274	12.5 × 15	0.27	0.73	430	258
68	680	10 × 25	0.21		0.57	526	326	12.5 × 15	0.23	0.62	466	289
82	820	10 × 31.5	0.18		0.49	606	386	16 × 15	0.19	0.51	681	433
100	101	10 × 31.5	0.15		0.41	663	438	16 × 15	0.17	0.46	719	475
120	121	12.5 × 25	0.13		0.35	774	519	16 × 15	0.14	0.38	793	531
150	151	12.5 × 25	0.11		0.30	798	553	18 × 15	0.12	0.32	917	635
180	181	12.5 × 31.5	0.098		0.26	904	641	16 × 20	0.11	0.30	995	706
220	221	12.5 × 35.5	0.087		0.23	1000	730	16 × 25	0.093	0.25	1170	854
270	271	12.5 × 40	0.072		0.19	1130	843	18 × 20	0.080	0.22	1230	918
330	331	16 × 31.5	0.062		0.17	1520	1160	18 × 25	0.070	0.19	1420	1080
390	391	16 × 35.5	0.053		0.14	1730	1340	18 × 31.5	0.062	0.17	1600	1240
470	471	16 × 40	0.047		0.13	1920	1530	18 × 35.5	0.056	0.15	1770	1410
560	561	18 × 35.5	0.041		0.11	2070	1680					
680	681	18 × 40	0.036		0.097	2300	1910					

※ In case of low profile type, [6] will be put at 12th digit of type numbering system.

Cap. (μF)	Code	160		200		250		315		350		400		450	
		2C		2D		2E		2F		2V		2G		2W	
1	010	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	10 × 12.5	21	10 × 12.5	17	10 × 15	17
2.2	2R2	8 × 11.5	30	8 × 11.5	30	10 × 12.5	32	10 × 12.5	32	10 × 15	34	10 × 15	28	10 × 20	28
3.3	3R3	10 × 12.5	50	10 × 12.5	50	10 × 15	52	10 × 15	52	10 × 20	54	10 × 20	47	12.5 × 20	48
4.7	4R7	10 × 12.5	57	10 × 15	60	10 × 15	60	10 × 20	65	10 × 20	65	12.5 × 20	55	12.5 × 25	55
10	100	10 × 15	90	10 × 20	95	12.5 × 20	98	12.5 × 20	98	12.5 × 25	100	12.5 × 25	85	16 × 25	90
22	220	12.5 × 20	140	12.5 × 25	145	16 × 25	150	16 × 25	150	16 × 25	150	16 × 31.5	130	16 × 35.5	135
33	330	12.5 × 25	175	16 × 25	180	16 × 25	180	16 × 31.5	185	16 × 35.5	190	18 × 35.5	170	18 × 40	170
47	470	16 × 25	220	16 × 25	220	16 × 31.5	225	18 × 35.5	235	18 × 40	240				
100	101	16 × 35.5	330	18 × 40	345	18 × 40	345							Case size	※ 1

※ 1 Rated ripple current (mA_{rms}) at 105°C 120Hz