

Power Schottky Rectifier - 30Amp 150Volt

Features

- Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- High Junction Temperature Capability
- Low forward voltage, high current capability
- High surge capacity
- Low power loss, high efficiency
- ESD performance human body mode > 6 KV

Application

- AC/DC Switching Adaptor and TFT-LCD Power Supply
- SMPS

Absolute maximum ratings


Symbol	Ratings	Unit	Conditions
$I_F(AV)$	30	A	Average Forward Current
V_{RRM}	150	V	Repetitive Peak Reverse Voltage
I_{FSM}	350	A	Peak Forward Surge Current
$V_F(max)$	0.72	V	Forward Voltage Drop
T_j	-50 to +175	°C	Operating Temperature
T_{stg}	-50 to +150	°C	Storage Temperature

Electrical characteristics

Parameters	Symbol	Ratings	Conditions
Maximum Instantaneous Forward Voltage	V_F	0.90V 0.72V	$T_c = 25^\circ C$ $T_c = 125^\circ C$
Maximum Reverse Leakage Current	I_R	0.01mA 10mA	$T_c = 25^\circ C$ $T_c = 125^\circ C$
Maximum Voltage Rate of Change	dv/dt	10,000 V/ μs	Rated V_R
Typical Thermal Resistance, Junction to Case	$R_{\theta(j-c)}$	1.25 °C/W	Per diode

Note: Pulse Test : 380 μs pulse width, 2% duty cycle

T0-247AD



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.748	.827	19.00	21.00	
B	.787	.866	20.00	22.00	
C	.598	.638	15.20	16.20	
D	.130	.150	3.30	3.80	
E	.205	.242	5.20	6.15	
F	.209	.232	5.30	5.90	
G	.077	.091	1.95	2.30	
H	.161	.189	4.10	4.80	
I	.551	.610	14.00	15.50	
J	.045	.055	1.15	1.40	
K	.197	.219	5.00	5.55	
L	.189	.205	4.80	5.20	
M	.020	.031	0.50	0.80	
N	.083	.094	2.10	2.40	
O	.116	.128	2.95	3.25	

September 2008 / Rev.6.2




Figure 1. Max. Forward Voltage Drop Characteristics (PerLeg)




Figure 2. Typical Values Of Reverse Current Vs. Reverse Voltage (PerLeg)




Figure 3. Typical Junction Capacitance Vs. Reverse Voltage (PerLeg)




Figure 4. Max. Thermal Impedance Z_{thJC} Characteristics (PerLeg)




Figure 5. Max. Allowable Case Temperature Vs. Average Forward Current (PerLeg)




Figure 6. Forward Power Loss Characteristics (PerLeg)




Figure 7. Max. Non-Repetitive Surge Current (PerLeg)